

# **PTZ Camera**

V2.820.1ATA000.0.R.240726

## **Release Notes**



ZHEJIANG DAHUA VISION TECHNOLOGY CO., LTD.



# **Table of Contents**

1 Release Notes	
1.1 Overview	1
1.2 New Features	
1.3 Fixed Bugs	
1.4 Compatibility	
1.4.1 Program	1
1.4.2 Browser	1
1.4.3 Third-party Access	2
1.5 Software Environment	
1.6 Pending Issues	2
2 Update Guide	3
2.1 Introduction	
2.2 Preparation	3
2.3 Instructions	3
2.3.1 Updating by ConfigTool	3
2.3.1.1 Updating One by One	3
2.3.1.2 Updating in Batches	5
2.3.2 Updating through the Webpage	6
2.3.3 Cloud Update through the Webpage	6
2.3.4 Cloud Update through DMSS	7
2.4 Checking for Update Success	7



# **1 Release Notes**

### 1.1 Overview

Product Name	PTZ Camera	
Version	V2.820.1ATA000.0.R.240726	
Software package information	DH_SD-Gram_MultiLang_PN_Stream3-Lingjing_V2.820.1ATA000.0.R.24 0726.zip	
OS requirement	None	
Release date	Jul 31, 2024	

### 1.2 New Features

No.	Feature Description
1	
2	
3	

# 1.3 Fixed Bugs

No.	Bug Description
1	Audio play was stuck.
2	
3	

# 1.4 Compatibility

### 1.4.1 **Program**

None.

### 1.4.2 Browser

- IE: 9 and later versions.
- Google Chrome: 41 and later versions.
- Firefox: 50 and later versions.
- Safari: 10 and later versions.



# 1.4.3 Third-party Access

• CGI: V2.91.3.12

ONVIF testing tool version: V23.06

• ONVIF: Supports Profile G, S, T

MILESTONE: Milestone XProtect Corporate 2023R3, device pack 13.0a

### 1.5 Software Environment

Category	Model	Version
	DSS pro	V8.003.0000000.0.R.20230421
Platform	ICC-B8900	V5.000.0000012.5.R.20221209
	DSS-C9100	V3.007.0000000.0.R.210330

# 1.6 Pending Issues

No.	Issue Description	Possible Result	How to Fix
1			
2			



# 2 Update Guide

#### 2.1 Introduction

This document provides multiple update methods. You can update the device to the latest version according to the update guide. The update methods include updating by ConfigTool and DMSS app, through local update package, and cloud update on the webpage.

### 2.2 Preparation

Before the update, please ensure that the following conditions are met.

- Update by ConfigTool: The device can work normally; the computer is installed with ConfigTool; the device is on the same network as the computer; the update package is ready.
- Update by local package: The device can work normally; the device is on the same network as
  the computer that is used to log in to the webpage; the update package is ready.
- Cloud update on the webpage: The device can work normally, and the device is on the same network as the computer that is used to log in to the webpage.
- Update by DMSS app: The device can work normally; the mobile phone is installed with DMSS app; the device is added to DMSS app.

 $\square$ 

- Decompress the program package before updating, otherwise the tool might not find the bin file to be updated.
- Check whether the device model and program version are correct before the update.

#### 2.3 Instructions

#### 2.3.1 Updating by ConfigTool

### 2.3.1.1 Updating One by One

Use this update method when you need to update a single device.

#### **Procedure**

- Step 1 Open ConfigTool, and then select **Device Upgrade**.
- **Step 2** Click **Search Setting** to set the search conditions.




D Configtool Ŧ You have selected 0 device(s) 0 111

Figure 2-1 Set search condition

Step 3 Select Current Segment Search, change the password to the PTZ camera password, and then click **OK**.





Step 4 Click next to the device to be updated, and then select the update file.

The update file is a bin file.

Step 5 Click 1 to start to update the system.

The device automatically restarts after the update is complete.

Check the system version after the device restarts.

If the system version is consistent with the version of the update package, the update is successful.

 $\square$ 

If the device update fails, update again in the following ways.

- Check whether the update file is correct; if the update file is incorrect, change the file to the correct one before update.
- Restart ConfigTool, and log in to this tool again to update the device.
- We recommend you use the latest version of ConfigTool.



#### 2.3.1.2 Updating in Batches

Use this method when you need to update multiple devices to the same software version.

#### **Procedure**

- <u>Step 1</u> Open ConfigTool, and then select **Device Upgrade**.
- <u>Step 2</u> Click **Search Setting** to set the search conditions.
- Step 3 Select **Current Segment Search**, change the password to the IPC password, and then click **OK**.




Figure 2-3 View search result

Step 4 Select the device to be updated, and then click **Batch Upgrade**.

You have selected 3 device(s)

<u>Step 5</u> Click **Browse** to select the update package.

Figure 2-4 Select update package



Step 6 Click **OK** to start to update the system.

The device automatically restarts after the update is complete.

Step 7 Check the system version after the device restarts.

If the system version is consistent with the version of the update package, the update is successful.

 $\square$ 

If the device update fails, update again in the following ways.

- Check whether the update file is correct; if the update file is incorrect, change the file to the correct one before update.
- Restart ConfigTool, and log in to this tool again to update the device.
- We recommend you use the latest version of ConfigTool.



#### 2.3.2 Updating through the Webpage

#### **Procedure**

- Step 1 Log in to the webpage of the device.
- Step 2 Select Setting > Maintenance Center > Update to enter the system update page.

Figure 2-3 System update



Step 3 Click **Browse**, select the bin file, and then click **Update**.

Do not cut off the power supply during the update process. The device automatically restarts when the update is complete.

- Step 4 After the restart, you are redirected to the login page for you to log in to the device again.
- Step 5 Check the system version after login.

If the system version is consistent with the version of the update package, the update is successful.

#### 2.3.3 Cloud Update through the Webpage

- Step 1 Log in to the webpage of the device.
- Step 2 Select Setting > Maintenance Center > Update to enter the system update page.

Figure 2-4 System update **O** General A Account System Version: 8 has assumed 4.8. Build Date: 2023-03-16 Online Undate Auto Check for Updates: d Option Manual Check New system version found: V3 management at J40500 Build Date 2023 d5 69 Supports Acurica File Update

Step 3 Click Manual Check.

Select Auto-check for updates, and when a new version is available, the device automatically

- Step 4 If a new version is available, click **Update Now**. The system downloads the version file and starts the update process.
- Step 5 After the restart, you are redirected to the login page for you to log in to the device again.
- Step 6 Check the system version after login. If the system version is consistent with the version of the update package, the update is successful.



#### 2.3.4 Cloud Update through DMSS

- Step 1 Log in to DMSS app.
- Step 2 Select Device Details.
- Step 3 Tap Cloud Update to go to the update page.

Figure 2-5 Update screen



#### Step 4 Tap Update.

Do not disconnect power supply or network from the device during update. After being updated successfully, the device will restart and connect to router .

Step 5 Check the system version after restart.

If the system version is consistent with the version of the update package, the update is successful.

# 2.4 Checking for Update Success

No matter which method is used, log in to the system again after the update is complete to check whether the version is correct.

