

4MP WiFi Video Doorbell

DH-DB41AB



Series Overview

The WiFi Video Doorbell is a new addition to the Dahua Wireless series. It not only delivers 2K high-resolution imagery, but also captures more details than conventional fixed lenses through its ultra-wide fisheye lens. The doorbell features passive IR motion detection and transmits videos and audios to mobile devices, allowing you to remotely perform visual confirmation and communicate with visitors. Furthermore, it is compatible with 2.4 GHz Wi-Fi 6 networks, enhancing its connectivity options.



4MP

Clear images with sharp details



H.265

Advanced H.265 compression technology



Supports Micro SD Card

Low-cost storage



One-click Proactive Call

Proactive bidirectional call anytime,



Al Human Detection

Focuses on what matters and reduces false alarms



Al Vehicle Detection

Focuses on what matters and reduces false alarms



Abnormal Sound Alarm

Detects abnormal sounds and sends alarms in time



Wi-Fi 6

Seamless integration of speed and anti-interference



Bluetooth Pairing

Fast pairing with Bluetooth



Upgrade Your Experience with DMSS

Dahua Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.













Specifications

Camera

Image Sensor 1/3" CMOS

Max. Resolution 2560 (H) × 1440 (V)

Illumination Distance Up to 10 m (32.81 ft) (IR)

Illuminator Number 2 (IR LED) Fixed-focal Lens Type Focal Length 2.3 mm Max. Aperture

Field of View H: 120°; V: 66°; D: 143°

Intelligence

Human Detection Yes Vehicle Detection Yes

Audio and Video

Video Compression H.265; H.264; H.264H; H.264B

Main stream: 2560 × 1440@(1–15 fps)/920 × 1080@

 $(1-15 \text{ fps})/1280 \times 720@(1-15 \text{ fps})$ Sub stream: $640 \times 360@(1-15 \text{ fps})$

Video Frame Rate *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.

H.264: 32 kbps-8192 kbps; Video Bit Rate H.265: 32 kbps-8192 kbps

Day/Night Auto(ICR)/Color/B/W

WDR DWDR

Motion Detection OFF/ON (4 areas, rectangular)

Image Rotation 0°/180°

Built-in MIC Yes, built-in Mic Yes, built-in speaker Built-in Speaker

G.711a; G.711Mu; PCM Audio Compression

Network

IEEE 802.11b/g/n/ax 2.4000-2.4835 GHz, 2.4 G,

EIRP≤20 dBm

Wi-Fi Pairing Bluetooth pairing

Micro SD card (support max. 256 GB)

Management Software DMSS

Mobile Client Android;iOS

General

CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive Certifications

2014/30/EU;

CE-RED: Radio Equipment Directive 2014/53/EU

USB (5 VDC±5%, 2 A) or binding post power supply **Power Supply** (10-24 VDC/14-24 VAC, 1.0 A)

Basic: 1.7 W (5 VDC); 2.1 W (10-24 VDC); 2.2 W

(14–24VAC, active power) Max.: 5.3 W (5 VDC); 6.8 W (10–24 VDC); 6.8 W (14– 24 VAC, active power) (IR + white light + alarm on) Power Consumption

Operating Temperature -20 °C to +55 °C (-4 °F to +131 °F)

Operating Humidity ≤95% (RH), non-condensing

Protection IP65

One-click Call Button Camera Button

Casing Material

135 mm × 45 mm × 24.2 mm (5.31" × 1.77" × 0.95") **Product Dimensions**

0.11 kg (0.24 lb) Net Weight

What's in the box



Installation Kit × 1

Mounting Bracket × 1



Documents:

information \times 1

Quick Start Guide × 1 Legal and regulation

Power:

Power Cable × 1











