

3MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera

DH-H3I



Series Overview

Wireless series cameras are not only easy to install and operate, but also perform outstandingly and cost-effective. They provide full coverage of a scene with 3MP resolution, 0° to 355° pan and-5° to 80° tilt. Their powerful functions, such as Al human and auto tracking, assist with the accurate detection and continuous tracking of targets. Information is also synchronously sent to your phone to keep you up-to-date. These cameras are widely used in small and medium-sized scenes such as small-sized retail stores.



3MP

Clear images with sharp details



Day&Night

Clear images even at night



One Camera for 360° View

360° monitoring without blind spots



Al Human Detection

Focuses on what matters and reduces false alarms



Auto Tracking

Automatic tracking of targets



One-click Privacy Mode

Protects your privacy



Abnormal Sound Alarm

Detects abnormal sounds and sends alarms in time



Wi-Fi 6

Seamless integration of speed and anti-interference



Bluetooth Pairing

Fast pairing with Bluetooth



H.265

Advanced H.265 compression technology



Supports Micro SD Card

Low-cost storage



Upgrade Your Experience with DMSS

Mobile Security Surveillance (DMSS) is a professional remote surveillance management platform that offers remote monitoring, device migration, and sharing. When connected to the internet, the platform provides real-time alerts to improve surveillance efficiency and grant flexibility in security management.













Specifications

Camera

1/3.2" CMOS Image Sensor

Max. Resolution 2304 (H) × 1296 (V)

Electronic Shutter Speed Auto/Manual 1/3 s-1/100,000 s

Up to 10 m (32.81 ft) (IR) Illumination Distance

Illuminator On/Off Control Auto Illuminator Number 1 (IR LED)

Pan: 0° to 355°; Tilt: -5° to 80° Angle Adjustment

Lens

F2.0 Max. Aperture

2.8mm H: 81°; V: 44°; D: 95° 3.6mm H: 69°; V: 36°; D: 81° Field of View

Intelligence

Human Detection Yes

Video

Video Compression H.265

Main stream: 2304 × 1296@15 fps sub stream: 640 × 360@15 fps *The values above are the max. frame rates of each Video Frame Rate

stream; for multiple streams, the values will be subjected to the total encoding capacity.

Resolution 3M (2304 × 1296); HD (640 × 360)

Video Bit Rate H.265: 80 kbps-4096 kbps Day/Night Auto(ICR)/Color/B/W

WDR DWDR Motion Detection Yes

0°/180° Image Rotation

Audio

Built-in MIC Yes, built-in Mic Built-in Speaker Yes, built-in speaker

Audio Compression G.711a

Network

Wi-Fi IEEE 802.11b/g/n/ax 2.412-2.472 GHz,2.4G

Storage Micro SD card (up to 256 GB)

DMSS Management Software

Mobile Client iOS;Android

Power

Power Supply 5 VDC

Basic: 1.9 W; Power Consumption Max.: 4.5 W (live + IR + PT rotation)

Environment

Operating Temperature -10 °C to +45 °C (+14 °F to +113 °F)

Operating Humidity ≤95% (RH), non-condensing

Structure

Plastic Casing Material

Product Dimensions φ90.9mm × 120.8 mm (φ3.58" × 4.76")

Net Weight 370 g (0.81lb)

What's in the box





















