

5MP WizColor Outdoor Wi-Fi Pan & Tilt Network

Camera

DH-P5F-PV

@lhua

Series Overview

The Wireless Compact Outdoor PT Camera sets a new standard for intelligent surveillance. In low-light conditions, it leverages WizColor technology to deliver crisp and vibrant images comparable to those captured in daylight without the need for additional lighting. Featuring advanced auto-tracking and preset patrol functions, it accurately detects humam and vehicles while minimizing false alarms. In the event of an intrusion, the camera activates sound and light alarms and promptly relays vital information to the mobile client, ensuring you stay informed no matter where you are.



5MP

Clear images with sharp details



AI-ISP

Provides a more vibrant, brighter image under low light conditions



Sound and Light Alarm

Provides instant alarms to deter intruders



Auto Tracking

Automatic tracking of targets



Al Human Detection

Focuses on what matters and reduces false alarms



AI Vehicle Detection

Focuses on what matters and reduces false alarms



One Camera for 360° View

360° monitoring without blind spots



Preset Patrol

Guards the places that matter to you regularly



IP66 Protection

Withstands harsh environments



Two-way Talk

Communication anytime, anywhere



Bluetooth Pairing

Fast pairing with Bluetooth



Wi-Fi 6

Seamless integration of speed and anti-interference



H.265

Advanced H.265 compression technology



Supports Micro SD Card

Low-cost storage



DMSS App

Easy to use



Upgrade Your Experience with DMSS

Intuitive AloT app for individual security



Remote Management

Live view and recording history



Easy sharing

Safer device sharing with family and friends



Notifications and Alerts

Accurate and timely



High Security

Stay secure with all data encrypted











Specifications

Camera

Image Sensor 1/1.8" CMOS Max. Resolution 2880 (H) × 1620 (V) Electronic Shutter Speed 1-1/100,000 s

0.0005 lux@F1.0 (Color, 30 IRE); Min. Illumination

0 lux (Illuminator on)

Illumination Distance 30 m (98.43 ft) (Warm light)

Illuminator Number 4 (Warm light)

Lens

Focal Length 3.6 mm Max. Aperture F1.0

Field of View H: 89.5°; V: 51°; D: 96°

PTZ

Pan/Tilt Range Pan: 0° to 345°; Tilt: 0° to 90°

Smart Event

Human Detection Yes Vehicle Detection

Video

Smart H.265+; H.265; Smart H.264+; H.264B; Video Compression H.264M; H.264H; MJPEG(Sub Stream 1)

Main stream: 5M/3M/720p@(1-25/30 fps) Video Frame Rate Sub stream 1: 640 × 360/QVGA@(1–25/30 fps)

Day/Night WDR 120 dB Motion Detection Yes Image Rotation 180°

Audio

Audio Compression PCM, G.711A, G.711Mu

Built-in MIC

Built-in Speaker **Network**

Network Port RJ-45 (10/100 Base-T)

IEEE802.11b; IEEE802.11g; IEEE802.11n; IEEE802.11ax Wi-Fi Standard

Wi-Fi Frequency Range 2.4 GHz Wi-Fi Transmission Rate 229 Mbps Wi-Fi Pairing Bluetooth pairing

Max. Transmission Power ≤20 dBm@2,400-2,483.5 MHz

ONVIF (Profile S & Profile G & Profile T); CGI; SDK Interoperability

Micro SD card (Up to 512 GB); FTP Storage

DMSS; NVR Management Software Mobile Client iOS; Android

Function

Abnormal Sound Alarm Yes

Certification

Certifications

Power

Power Supply 12 VDC, 1 A ± 10%

Power Consumption Max. (Basic power consumption + WDR + light on + PTZ operation): 9 W

Environment

-30 °C to +55 °C (-22 °F to +131 °F) Operating Temperature

Operating Humidity ≤95%

IP66; TVS 2000 V lightning proof; surge protection; Protection voltage transient protection

Structure

Product Dimensions 153.5 mm × Φ129.3 mm (6.04" × Φ5.09")

Net Weight 0.60 kg (1.32 lb)

What's in the box



Installation Position







Mounting Plate × 1



Waterproof Connector





Certification × 1

Documents:

QR Code × 1



Wireless Frequency Band Paper × 1 (Only for-EUR)

Quick Start Guide × 1

Legal and regulation

information $\times 1$



Warranty Card × 1 (Only for-EUR)



