

DH-PFB2112C

Ceiling Mount Bracket



Series Overview

The Mounting Bracket works with front-end services, supporting installation methods such as wall mount, pole mount, corner mount and in-ceiling mount. Select brackets are designed to suit complex scenes, making them convenient to use in environments with high temperatures, humidity, frequent vibrations, and in locations that are highly corrosive. These highly reliable brackets are easy to install and use.

Scene

Compatible with cameras, and works in temperatures ranging from $-40\,^{\circ}\text{C}$ to $+60\,^{\circ}\text{C}$ ($-40\,^{\circ}\text{F}$ to $+140\,^{\circ}\text{F}$) and in environments with a relative humidity of less than 90%. Avoid installing in areas with severe vibration or where the bracket might easily hit people.

Technical Specification

Structure

Casing Material	SPCC; Aluminum alloy
Product Dimensions	Φ 120.0 mm × 1030.0 mm $-\Phi$ 120.0 mm × 1800.0 mm (Φ 4.72" × 40.55" $-\Phi$ 4.72" × 70.87")
Appearance Color	White
Net Weight	1.04 kg (2.29 lb)
Gross Weight	1.56 kg (3.44 lb)
Load Bearing	2.0 kg (4.41 lb)
Installation	Ceiling mount
Adjustable Inclination Angle	-60° to +60°
Applicable Model	Please see "Camera Accessories Selection"

- · Built of aluminum alloy and SPCC material, it is cost-effective.
- · Suitable for a variety of cameras and is elegant.
- Supports being adjusted to multiple angles to suit the needs of various installation locations.
- · It can be scaled from 1030 mm to 1800 mm.



Packaging Dimensions





0 0	$(L \times W \times H)$	
Environment		
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)	
Operating Humidity	< 90% (RH)	
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)	
Storage Humidity	10%-90% (RH)	
Anti-corrosion Level	Basic Protection *The products are designed for general use and are applicable even in areas with no specific requirements	

1031 mm × 168 mm × 175 mm (40.59" × 6.61" × 6.89")

Ordering Information


Туре	Model	Description
Camera Mount	DH-PFB2112C	Ceiling Mount Bracket

Installation



Dimensions (mm[inch])

mm [inch]



Package Information

- · Ceiling mount bracket $\times 1$
- Mounting sticker × 1
- \cdot 1/4-20×8 UNC screws × 2
- \cdot 1/4-20×12 UNC screws × 1
- M6 × 8 screws ×2
- M6 ×12 screws ×1
- · S3.0 wrench ×1