

DHI-SCP3044A-BZ

4-Wire Hybrid Smart Control Panel



Functions

Smart Control Panel

Features multiple functions such as video intercom, video monitoring and wireless alarm. Its Android 14 system supports the installation of APK files, allowing for the expansion of third-party applications.

Scene

It is ideal for villas, communities, apartments and hotels, and is well suited for offices.

Technical Specification		
System		
Main Processor	Embedded Processor	
Operating System	Android 14	
Network Protocol	IPv4;RTSP;UDP;DNS;FTP;RTP;TCP;SIP	
Basic		
Screen Type	Capacitive Touchscreen	
Display Screen	10.1-inch display screen	
Screen Resolution	1280 (H) × 800 (V)	
Audio Compression	G.711a; G.711u; PCM	
Audio Input	1 channel	
Audio Output	Built-in speaker	
Audio Mode	Two-way audio	
Audio Enhancement	Echo suppression/digital noise reduction	
Audio Bit Rate	16 kHz, 16 bit	
Function		
Communication Mode	Full digital	

- Adopts the Android 14 system, offering advanced performance and a user-friendly experience.
- Featuring a sleek full-screen design with an ultra-narrow black border, this device combines style and minimalism for an exceptional visual experience.
- With its 10.1-inch IPS capacitive touchscreen and multi-touch technology, the screen offers wide viewing angles of up to 80 degrees both horizontally and vertically, significantly enhancing work efficiency and operational flexibility.
- Supports multiple communication modes including IP, Wi-Fi and IP four-wire.
- Includes multi-color indicators that feature the breathing light function to keep you updated on status changes.
- Wakes up automatically when a person approaches for a seamless experience.
- Equipped with a built-in light sensor, the device automatically adjusts the screen brightness for comfortable viewing.
- With its built-in temperature and humidity detectors, you can effortlessly monitor the conditions in your house at any time straight from the home screen.


Information Release	Receive and view the published information from the management center
Elevator Control	Residents can call the elevator through this device to their floor.
Leave Videos	Yes (SD card is inserted in the indoor monitor or door station)
DND Mode	Do not disturb period can be set
Number of Extensions	Villa: 1 main VTH and 9 extensions Apartment: 1 main VTH and 4 extensions
Expansion Module	ZigBee module Wireless 868 MHz Sensor Bluetooth module
Storage	Supports micro SD card storage (up to 512 GB)
Network	
Wi-Fi	Yes
Wireless Standard	IEEE 802.11a/b/g/n/ac/ax
Wireless Frequency Range	2.4 GHz; 5 GHz
Port	
RS-485	1
USB	1

DHI-SCP3044A-BZ


Alarm Input	8 channels	
Alarm Output	1 channel	
Power Output	1 port (12 V, 200 mA)	
Door Bell	Yes (use the alarm input port)	
Network Port	$1 \times 10/100$ Mbps Ethernet port	
4-wire	1	
Performance		
Casing Material	PC + ABS	
General		
Appearance Color	Gray	
Power Supply	12 VDC, 2 A Standard PoE	
Power Adapter	Optional	
Installation	Flush Mount	
Certifications	CE	
Accessory	Included: RS-485 and power output cable, bracket and alarm cable. Optional: Power cord	
Product Dimensions	246.5 mm × 156.1 mm × 33.0 mm (9.70" × 6.15" × 1.30") (H × W × D)	
Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)	
Operating Humidity	10%–95% (RH), non-condensing	
Operating Altitude	Below 3,000 m (9,842.52 ft)	
Power Consumption	≤ 12 W (standby), ≤ 15 W (working)	
Gross Weight	1,291 g (2.85 lb)	
Storage Temperature	0 °C to +40 °C (+32 °F to +104 °F)	
Storage Humidity	30%-75%	
Operating Environment	Indoor	

Ordering Information				
Туре	Model	Description		
Smart Control Panel	DHI-SCP3044A-BZ	4-Wire Hybrid Smart Control Panel		

Installation



Dimensions (mm[inch])



Application

