

DHI-NVR2108HC-W

Dahua 8CH 1HDD Cooper 1U WIRELESS NETWORK RECORDER



Series Overview

With its advanced system, the Dahua Wireless Series NVR performs optimally, automatically detecting and connecting to Wi-Fi cameras to instantly generate live videos. It comes with an embedded Wi-Fi module that supports a wide range of Wi-Fi standards, including IEEE 802.11b/g/n/a/ac/ax. Equipped with dual high-gain antennas, its signals are highly stable, covering an extensive area, enabling the NVR to deliver reliable wireless connectivity. Additionally, the NVR features AP mode for creating dedicated surveillance networks, as well as Station mode for ensuring stable transmission and unparalleled deployment flexibility. Its unique design eliminates the need for network cables, making it a convenient solution for integrating wireless cameras into surveillance systems for small to medium-sized businesses. Ideal for houses, cafés, supermarkets, retail stores, and various other locations, the Dahua Wireless Series NVR is a practical choice for modern surveillance needs.

Functions

6th Generation Wi-Fi

With its embedded Wi-Fi 6 module, the Wi-Fi NVR is not only highly stable, but also offers fast transmission rates, low-latency and extensive coverage, enabling efficient and reliable monitoring.

SMD Plus

With intelligent algorithm, Dahua Smart Motion Detection technology can categorize the targets that trigger motion detection and filter the motion detection alarm triggered by non-concerned targets to realize effective and accurate alarm.

- · Automatic pairing with wireless cameras.
- Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.
- Max. decoding capability: 10 × 1080p@30 fps or 4 × 5MP@30 fps.
- Max. 80/80/80 Mbps incoming/recording/outgoing bandwidth.
- · Supports IP cameras with a resolution up to 16 MP.
- · Al by Recorder supports 4-channel SMD Plus.
- · Al by Camera supports perimeter protection and SMD.
- · Supports one-click arming and disarming.











Perimeter Protection by Camera


Automatically filters out false alarms caused by animals, rustling leaves, bright lights, etc. Enables system to act secondary recognition for the targets. Improves alarm accuracy.


Technical Specification		Wi-Fi	Wi-Fi	
System		Wi-Fi Standard	802.11b/g/n/a/ac/ax	
Main Processor	Industrial-grade processor	Frequency Range	2400-2483.5MHz, 5150-5350MHz, 5470-5725MHz, 5725-5850MHz	
Operating System	Embedded Linux		CE EIRP: ≤20dBm@2400-2483.5MHz; ≤23dBm@5150-5250MHz; ≤20dBm@5250-5350MHz; ≤27dBm@5470-5725MHz;	
Operating Interface	Web, Local GUI	Transmitter Power (EIRP)		
Al		nansmitter rower (EIRF)		
Al by Recorder	SMD Plus		≤14dBm@5725-5850MHz	
AI by Camera	Perimeter protection; SMD	Recording Playback		
Perimeter Protection		Multi-channel Playback	Up to 8 channels	
Perimeter Performance of AI by Camera (Number of Channels)	All channels (8 targets/s)	Record Mode	General, motion detection; intelligent; alarm	
		Backup Method	USB device and network	
SMD		Playback Mode	Instant playback; general playback; event playback; tag playback; smart playback	
SMD Plus by Recorder	4 channels: Secondary filtering for human and motor vehicle, reducing false alarms caused by leaves, rain and	Alarm		
SWID THAS BY RECORDER	lighting condition change	General Alarm	Motion detection; camera external alarm; PIR alarm	
SMD by Camera	All channels (16 targets/s)		Error (no disk, disk error, low space, low quota space; network disconnection; IP conflict; MAC conflict); video loss; video tampering; camera offline	
Audio and Video		Anomaly Alarm		
Access Channel	8 channels	Intelligent Alarm	Perimeter protection; SMD Plus	
	Al disabled: 80 Mbps incoming, 80 Mbps recording and 80 Mbps outgoing	Alarm Linkage	Recording; snapshot; buzzer; log; preset; email; tour	
Network Bandwidth	Al enabled: 80 Mbps incoming, 80 Mbps recording and 60 Mbps outgoing	Port		
Resolution	16 MP; 12 MP; 8 MP; 6 MP; 5 MP; 4 MP; 3 MP; 1080p; 960p; 720p; D1; CIF; QCIF	Disk Interface	1 SATA port. Each disk can contain up to 20 TB. This limit varies depending on the environment temperature.	
	Al disabled: 1-channel 16 MP@30 fps; 2-channel 8 MP@30 fps; 3-channel 6 MP@30 fps; 4-channel 5 MP@30 fps; 5-channel 4 MP@30 fps; 6-channel 3 MP@30 fps; 8-channel 2 MP@30 fps Al enabled: 1-channel 12 MP@30 fps; 2-channel 6 MP@30 fps; 3-channel 4 MP@30 fps; 4-channel 3 MP@30 fps; 6-channel 1080p@30 fps; 8-channel 720p@30 fps	USB	2 (2 rear USB 2.0 ports)	
		HDMI	1	
Decoding Capability		VGA	1	
		Network Port	1 (10/100 Mbps Ethernet port, RJ-45)	
		Antenna	2	
	1 HDMI, 1 VGA HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720	General		
Video Output		Power Supply	12 VDC, 1.5 A	
	VGA: 1920 × 1080, 1280 × 1024, 1280 × 720	Power Consumption	<6 W (without HDD)	
Multi-screen Display	1/4/8/9	Net Weight	0.57 kg (1.26 lb)	
Third-party Camera Access	ONVIF	Gross Weight	0.98 kg (2.16 lb)	
Compression Standard		Product Dimensions	197.0 mm × 234.0 mm × 41.5 mm (7.76" × 9.21" × 1.63") (W × D × H)	
Video Compression	Smart H.265+; H.265; Smart H.264+; H.264; MJPEG		332.0 mm × 240.0 mm × 64.0 mm (13.07" × 9.45" ×	
Audio Compression	G.711a; G.711u; PCM; G726	Packaging Dimensions	2.52") (W × D × H)	
Network		Operating Temperature	-10 °C to +45 °C (+14 °F to +113 °F)	
Network Protocol	HTTP; HTTPS; TCP/IP; IPv4; IPv6; UDP; NTP; DHCP; DNS; SMTP; IP Filter; DDNS; IP Search (Supports IP camera, DVR, NVS, etc.); P2P; Auto Registration	Storage Temperature	-20 °C to +60 °C (-4 °F to +140 °F)	
		Operating Humidity	10%–93% (RH), non-condensing	
Mobile Phone Access	iOS; Android	Certifications	CE-LVD: IEC 62368-1:2014 CE-EMC: EN IEC 61000-3-2:2019, EN 61000-3-3:2013+A1:2019, EN 55032:2015+A11:2020, EN 55035:2017+A11:2020, EN 55024:2010+A1:2015, EN 50130-4:2011+A1:2014	
Interoperability	ONVIF 24.12(Profile T; Profile S; Profile G); CGI; SDK			
Browser	Chrome; IE; Safari; Edge; Firefox			

Lite Series | DHI-NVR2108HC-W


Ordering Information				
Туре	Model	Description		
NETWORK VIDEO RECORDER	DHI-NVR2108HC-W	Dahua 8CH 1HDD Cooper 1U WIRELESS NETWORK RECORDER		

Dimensions (mm[inch])





Panels



- 1 Ground
- 3 Power Input
- 5 VGA Port
- 7 USB Ports

- 2 Antenna Port
- 4 Network Port
- 6 HDMI Port