

## 8MP WizColor Outdoor Wi-Fi Pan & Tilt Network Camera

DH-P8F-PV

#### **Series Overview**

The Compact Outdoor PT Camera functions optimally, offering stunning ultra-clear 4K resolution. In low-light conditions, it leverages WizColor technology to deliver crisp and vibrant images comparable to those captured in daylight without the need for additional lighting. Featuring advanced auto-tracking and preset patrol functions, it accurately detects humam and vehicles while minimizing false alarms. In the event of an intrusion, the camera activates sound and light alarms and promptly relays vital information to the mobile client, ensuring you stay informed no matter where you are





Provides a more vibrant, brighter image under low light conditions

	Al Human Dete
	Focuses on what ma reduces false alarms

AI-ISP

uman Detection es on what matters and



**Preset Patrol** Guards the places that matter to you regularly



**Bluetooth Pairing** Fast pairing with Bluetooth



**Supports Micro SD Card** Low-cost storage





Provides instant alarms to deter intruders

	$\frown$
1	
	$\sim$

**AI Vehicle Detection** 

Focuses on what matters and reduces false alarms



**IP66 Protection** Withstands harsh environments



Wi-Fi 6 Seamless integration of speed and anti-interference

**DMSS App** Easy to use



## **Upgrade Your Experience with DMSS**

Intuitive AIoT app for individual security

Accurate and timely





**Notifications and Alerts** 



#### **Easy sharing**

Safer device sharing with family and friends



**High Security** Stay secure with all data encrypted











# **Specifications**

1/1.8" CMOS

3840 (H) × 2160 (V)

0.0005 lux@F1.0 (Color, 30 IRE); 0 lux (Illuminator on)

30 m (98.43 ft) (Warm light)

H: 82.9°; V: 47.3°; D: 93.4°

Pan: 0° to 345°; Tilt: 0° to 90°

Smart H.265+; H.264M; H.264H; Smart H.264+;

Sub stream 1: 640 × 360/QVGA@(1–15 fps)

H.265; H.264B; MJPEG(Sub Stream 1) Main stream: 8M/3M/720p@(1-15 fps)

1 s-1/100,000 s

4 (Warm light)

3.6 mm

F1.0

Yes

Yes

Color/B/W

120 dB

Yes

180°

#### Camera

Image Sensor Max. Resolution

Electronic Shutter Speed

Min. Illumination

Illumination Distance

Illuminator Number

#### Lens

Focal Length Max. Aperture Field of View

#### PTZ

Pan/Tilt Range

#### Smart Event

Human Detection

#### Vehicle Detection

#### Video

Video Compression

Video Frame Rate

Day/Night

WDR

Motion Detection Image Rotation

#### Audio

Audio Compression Built-in MIC

PCM, G.711A, G.711Mu Yes

L

# What's in the box

Tools: Installation Position •• Map × 1 D Screw Package × 1 Mounting Plate × 1 2

Waterproof Connector 8 x 1

QR Code × 1 Power Adapter × 1 Quick Start Guide × 1 Legal and regulation information × 1 Certification × 1 Π Wireless Frequency

Documents:



Warranty Card × 1 (Only for-EUR)

## Built-in Speaker

### **Network**

Network Port Wi-Fi Standard Wi-Fi Frequency Range Wi-Fi Transmission Rate Wi-Fi Pairing Max. Transmission Power Interoperability Storage Management Software Mobile Client

### **Function**

Abnormal Sound Alarm

#### Certification

Certifications

**Power** Power Supply

Power Consumption

#### **Environment**

Operating Temperature Operating Humidity

Protection

#### **Structure**

Product Dimensions Net Weight

Power:



RJ-45 (10/100 Base-T)
IEEE802.11g;IEEE802.11b; IEEE802.11n; IEEE802.11ax
2.4 GHz
229 Mbps
Bluetooth pairing
≤20 dBm@2,400-2,483.5 MHz
ONVIF (Profile S & Profile G & Profile T); SDK; CGI
Micro SD card (Up to 512 GB); FTP
NVR;DMSS
Android;iOS
Yes
CE
12 VDC, 1 A ± 10%
Basic: 3 W
Max. (Basic power consumption + WDR + Light on + PTZ operation): 9 W
. ,
−30 °C to +55 °C (−22 °F to +131 °F)
≤95%
IP66; TVS 2000 V lightning proof; surge protection;
voltage transient protection
153.5 mm × Φ129.3 mm (6.04" × Φ5.09")
0.60 kg (1.32 lb)

