

DH-IPC-UDW3859T-S-PRO

8MP WizColor Fixed-focal Eyeball WizSense + Network Camera





Launched by Dahua Technology, WizSense + is a series of AI products and solutions that adopt independent AI chip and deep learning algorithm. It focuses on human and vehicle with high accuracy, enabling users to fast act on defined targets. Based on Dahua's advanced technologies, WizSense + provides intelligent, simple and inclusive products and solutions.

Series Overview

With advanced deep learning algorithm, Dahua WizSense + 3 Series network camera supports intelligent functions, such as perimeter protection and smart motion detection. With starlight technology, this series camera provides a better image effect in the condition of low illuminance.

Functions

WizColor Technology

Dahua WizColor Technology seamlessly combines with the powerful AI-ISP, large pixel size sensor and large aperture in cameras. This unique integration enables cameras to effortlessly capture high-quality images with vibrant colors during nighttime scenarios, ensuring fine details are preserved and minimizing motion blur. Unlike traditional self-illuminating cameras, Dahua WizColor Technology maximizes the utilization of weak light sources, such as moonlight and city lights reflected in the sky, delivering captivating full-color images of the entire scene. It also ensures that monitoring distances are not compromised at night due to limited illumination ranges, facilitating full-color image capture even over long distances.

AI-ISP

With AI ISP technology, the camera is able to easily adapt to scenes, producing high quality images that reveal the fine details of targets.

SMD Plus

With intelligent algorithm, Dahua Smart Motion Detection technology can categorize the targets that trigger motion detection and filter the motion detection alarm triggered by non-concerned targets to realize effective and accurate alarm.

- 8-MP 1/1.8" CMOS image sensor, low luminance, and high definition image.
- Outputs max. 8 MP (3840 × 2160)@20 fps, and supports 4 MP (2688 × 1520)@25/30 fps.
- · H.265 codec, high compression rate, ultra-low bit rate.
- · Built-in warm light, and the max. illumination distance is 30 m.
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments.
- Rotation mode, WDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.
- Intelligent monitoring: Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and human)
- Abnormality detection: Motion detection, video tampering, audio detection, no SD card, SD card full, SD card error, network disconnection, IP conflict, illegal access, and voltage detection.
- · Supports max. 256 G Micro SD card; built in Mic.
- 12 VDC/PoE power supply, easy for installation.
- IP67 protection.
- SMD Plus















Perimeter Protection

With deep learning algorithm, Dahua Perimeter Protection technology can recognize human and vehicle accurately. In restricted area (such as pedestrian area and vehicle area), the false alarms of intelligent detection based on target type (such as tripwire, intrusion, fast moving, parking detection, loitering detection and gathering detection) are largely reduced.

Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, Dahua smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

Protection (IP67, Wide Voltage)

IP67: The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can work normally after soaking in 1 m deep water for 30 minutes. Wide voltage: The camera allows $\pm 30\%$ (for some power supplies) input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

by the sub stream)

Technical Specification							Smart Codec	Smart H.265+; Smart H.264+
Camera								Main stream: 3840 × 2160@(1–20 fps)/2688 ×
Image Sensor		1/1.8" CMOS						1520@(1–25/30 fps) sub stream: 704 × 576@(1–25 fps)/704 × 480@(1–30
Max. Resolution		3840 (H) × 2160 (V)					Video Frame Rate	fps) *The values above are the max. frame rates of
ROM		128 MB						each stream; for multiple streams, the values will be subjected to the total encoding capacity.
RAM		256 MB					Streaming Capability	2 streams
Scanning System		Progressive						8M (3840 × 2160); 6M (3072 × 2048); 5M (3072 ×
Electronic Shutter Speed		Auto/Manual 1/3 s–1/100,000 s					Resolution	1728/2880 × 1620); 4M (2688 × 1520); 3M (2048 × 1536/2304 × 1296); 1080p (1920 × 1080); 1.3M (1280
Min. Illumination		0.0008 lux@F1.0					VC	× 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF (352 × 288/352 × 240)
S/N Ratio		>56 dB						VBR;CBR
Illumination Distance		Up to 30 m (98.43 ft) (Warm light)					H 264-32 khns-8192 khns-	
Illuminator On/Off Control		Auto;Manual					Video Bit Rate	H.265: 12 kbps–8192 kbps
Illuminator Number		2 (Warm light)					Day/Night	Color/B/W
Angle Adjustm	ant	Pan: 0° – 360°					BLC	Yes
Angle Adjustment		Tilt: 0°– 78° Rotation: 0°–360°					HLC	Yes
Lens							WDR	120 dB
Lens Type		Fixed-focal					White Balance	Auto; natural; street lamp; outdoor; manual; regional custom
Lens Mount		M16					Gain Control	Auto/Manual
Focal Length		2.8 mm; 3.6 mm					Noise Reduction	3D NR
Max. Aperture		F1.0					Motion Detection	OFF/ON (4 areas, rectangular)
Field of View		2.8 mm: H: 110°; V: 59°; D: 131° 3.6 mm: H: 93°; V: 49°; D: 110°					Region of Interest (RoI)	Yes (4 areas)
Iris Control		Fixed					Smart Illumination	Yes
Close Focus Distance		2.8 mm: 2.8 m (9.19 ft) 3.6 mm: 4 m (13.12 ft)					Image Rotation	$0^{\circ}/90^{\circ}/180^{\circ}/270^{\circ}$ (Support $90^{\circ}/270^{\circ}$ with 2688×1520 resolution and lower)
	Lens	Detect	Observe	Recognize	Identify		Mirror	Yes
	2.8 mm	84.0 m	33.6 m	16.8 m	8.4 m		Privacy Masking	4 areas
	2.0		(110.24 ft)	(55.12 ft)	(27.56 ft)		LDC	Yes
DORI	3.6 mm	102.0 m (334.65 ft)	40.8 m (133.86 ft)	20.4 m (66.93 ft)	10.2 m (33.46 ft)		Audio	
Distance	*DORI (Detect, Observe, Recognize, Identify) is a standard system						Built-in MIC	Yes, built-in Mic
	(EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area.						Audio Compression	G.711a; G.711Mu; PCM; G.726
		The numbers in this table do not reflect intelligent function distances. For intelligent function distances, refer to installation					Alarm	
		oning manual			stallation			No SD card; SD card full; SD card error; network disconnection; IP conflict; illegal access; motion
Intelligence							Alarm Event	detection; video tampering; tripwire; intrusion; audio detection; voltage detection; SMD; security exception
IVS (Perimeter Protection)		Intrusion, tripwire (the two functions support the classification and accurate detection of vehicle and					Network	
		human)					Network Port	RJ-45 (10/100 Base-T)
SMD		SMD Plus					SDK and API	Yes
Smart Search		Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos					Network Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; P2P; Bonjour;
Video							Interonerability	Auto Registration ONVIE (Profile S & Profile G & Profile T): CGI
Video Compression		H.265; H.264; H.264H; H.264B; MJPEG (Only supported by the sub stream)					Interoperability	ONVIF (Profile S & Profile G & Profile T); CGI

	711 11 0 0 D W 0 0 0 5 1 0 1 1 K 0	
User/Host	20 (Total bandwidth: 48 M)	
Storage	FTP; SFTP; Micro SD card (support max. 256 GB); NAS	
Browser	IE; Chrome; Firefox	
Management Software	Smart PSS Lite; DSS; DMSS	
Mobile Client	iOS;Android	
Security	Digest;WSSE;Account lockout;Security logs;IP/MAC filtering;Generation and importing of X.509 certification;syslog;HTTPS;802.1x;Trusted boot;Trusted execution;Trusted upgrade;Session security;Security warning	
Certification		
Certifications	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU	
Power		
Power Supply	12 VDC (±30%); PoE (802.3af)	
Power Consumption	Basic: 2.4 W (12 VDC); 3 W (PoE) Max.: 5.6 W (12 VDC); 6.4 W (PoE) (H.265+ intelligence on + WDR + illuminator intensity)	
Environment		
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)	

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)	
Operating Humidity	≤95% (RH), non-condensing	
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)	
Storage Humidity	≤95% (RH), non-condensing	
Protection	IP67	

Structure Casing Material Inner core: Metal; Cover: Plastic Product Dimensions 109.5 mm × Ф109.9 mm (4.31" × Ф4.33")

0.42 kg (0.93 lb)

0.59 kg (1.30 lb)

Net Weight

Gross Weight

Ordering Information					
Type	Model	Description			
IP CAMERA	DH-IPC-UDW3859T-S-PRO	8MP WizColor Fixed-focal Eyeball WizSense + Network Camera			
	DH-PFA109	Mount Adapter			
	DH-PFB220C	Ceiling Mount Bracket			
	DH-PFA151	Corner Mount Bracket			
	DH-PFB305W	Wall Mount Bracket			
Accessories (Optional)	DH-PFA150	Pole Mount Bracket			
	DH-PFB205W-E	Wall Mount Bracket			
	DH-PFA152-E	Pole Mount Bracket			
	DH-PFA13G	Junction Box			
	DH-PFM321-EN	DC12V1A power adapter			

Туре	Model	Description
	DH-PFM320D-EN	DC12V2A power adapter
	PFM900-E	Integrated Mount Tester
	DHI-TF-W100-256GB	MicroSD Card
	DHI-TF-P100/256GB	MicroSD Card

Accessories

Optional:



DH-PFA109 Mount Adapter



DH-PFA13G Junction Box



DH-PFA150 Pole Mount Bracket



DH-PFA151 Corner Mount Bracket



DH-PFA152-E Pole Mount Bracket



DH-PFB205W-E Wall Mount Bracket



DH-PFB220C Ceiling Mount Bracket



DH-PFB305W Wall Mount Bracket



DH-PFM320D-EN DC12V2A power adapter



DH-PFM321-EN DC12V1A power adapter



DHI-TF-P100/256GB MicroSD Card




DHI-TF-W100-256GB MicroSD Card



PFM900-E Integrated Mount Tester





Dimensions (mm[inch])

mm [inch]

